

Data Center Checklist

Fully-Welded Four-Post Frame	Structural integrity support
Impressive Static Load Capacity	High weight-load capacity
Strong Dynamic Load Capacity	Rolling high-weight capacity
Flush-Mount Doors/Side Panels	Coincides with floor tile dimensions, prevents aisle creep
Split-Rear Door Option	Promotes ease of access in narrow aisles
Solid Door Option	Supports containment applications
Lift-Off Door Hinges	Simple door installation and removal
Integrated RFID Tagging	Supports asset tracking
Grounding Option	Minimize ESD and RF interference

Half-Height Side Panel option (Exterior or Interior)	Light weight for ease of handling
Electronic Door Lock Upgrade	Secure access/monitoring to meet corporate compliance requirements
PDU/Cable Management Plates	Mounting of industry standard PDUs/Tool-less cable management accessories
Adjustable, Movable PDU Cable Management Plates	Mount multiple plates to accommodate multiple and larger PDUs
Variety of Heights: 42U, 45U, 48U, 51U	Range of height supports both single-tenant and colocation needs
Choice of depths: 42" and 48"	Supports deeper equipment, maximizes airflow efficiency through open cable management
Choice of widths: 24" and 30"	30" wide supports intensive cable management requirements and does not obstruct equipment
Easily Tailored to Customer Requirements	Even more features and benefits available – speak with a sales or customer service rep about your site-specific needs